	8 7	6	5	. 4	3	2	1		
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.				REV	REVISIONS	DATE	APPROVED	-
	WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.				A INITIAL RELEASE		3/15/18	D.FRISIELLO	_
									-
									-
D			0	.25					D
				7.2]					
				/.2]					
				ج <u>)</u>					
				-50 [12.7					
			Ø.203						
			[5.2]	[7.9]]				
С									
C									С
		-	1.50						
	[25.3]		[38.1]						
		-	▼						
		,							
-		ן בי	.04 6.3]						
			0.3						
		<u> </u>		2.63					
		.97	Τ	[66.9]					
		[24.6]							
В									В
		I		V					
		LABEL							
				UNLESS OTHERWISE SPECIFIED,	APPROVALS DATE	Global		GH STREET	1
	NOTES:				DRAWN BY D.FRISIELLO 3/15/18			NDOVER, MA 1845	
А	1. HARDWARE INCLUDED.			OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] 560 [1524] +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	CHECKED BY M.MARTINEZ 3/15/18	CATEGORY			A
				>60 [1524] <120 [3048] = +4 [102] / -0 >120 [3048] <300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	APPROVED BY M.MARTINEZ 3/15/18	RF LIGHTNING	PROTECTO	RS	
	2. COMPONENT SHALL BE INDIVIDUALLY PA ACCORDANCE WITH L-COM SPECIFICA	ackaged in TION PS-0031.		ALL OTHER DIMENSIONIAL TOLERANCES.	CONFIGURATION DETAILS OF	PRODUCT DESCRIPTION			1
				$\begin{array}{c} X = \pm .2 \ [5.08] \\ XX = \pm .02 \ [.51] \\ XXX = \pm .005 \ [.13] \end{array}$	UNDIMENSIONED FEATURES MAY VARY	BROADBAND 1	.5-700MHz F	250	
	REGULATORY COMPLIANCE: CE2011/65/EU(RoHS DIRECTIVE)			PROJECTION	COLOR VARIATIONS MAY OCCUR	SIZE FSCM NO. DWG. NO. 43321	LCSP1032	REV.	
					MATOCCUK	SCALE: NONE CAD FILE: LCSP1032.		SHEET 1 OF 1	-
	8 7	6	5	↑ 4	3	2	1		L
	- ,	-	-		-	-			