			REVISION		
		REV.	DESCRIPTION INITIAL RELASE	DATE 01/31/20	APPROVED S.ELLIS
				0.00120	
Ø.240 [6.10]	JACKET SHIELD LA SHIELD LA				
	SOLID CE	CTRIC	DUCTOR		
	$\label{eq:calibration} \begin{array}{c} \mbox{CABLE LENGTH (L) TOLERANCES:} \\ \mbox{$L \le 12$ [305] = +1 [25] / -0$} \\ \mbox{$12$ [305] < L \le 60 [1524] = +2 [51] / -0$} \\ \mbox{$01$ [1524] < L \le 120 [3048] = +4 [102] / -0$} \\ \mbox{$120 [3048] < L \le 300 [7620] = +6 [152] / -0$} \end{array}$	0 High Street North A Phone: 1.80 Fa Web	an INFINIT® brand West Mill, 3rd Floor, Suite Indover, MA 01845 USA. 0.341.5266 1.978.682.69 ax: 1.978.689.9484 site: www.L-com.com stomerService@L-com.com	2 #30 936 SCALE	GLE PROJECTION CORMATION AND THIS DOCUMENT PROPERTY OF BAL CONNECTIVITY SHTS RESERVED. 1 0F 1 N/A
THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	E CAGE CODE	DRAWN BY ITEM NO.	LMR-240	REV A