THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR	REVISIONS	
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.	REV DESCRIPTION A INITIAL RELEASE	DATE APPROVAL 02/22/2021 GUTTADAURO
TSFC6-XXX-XXXF CONSISTS OF A CONTINUOUS LENGTH OF B	ULK CABLE	
	ALUM/POLY CROSS-SECTI	
	SHIELD, (PAIR)	
	JACKET WHT	WHI
		X BLU
	SHIELD	\times
	WHT X	X X
	GRN	ORG
	COLOR (WHITE)	
	WHITE/OR WHITE/O	REEN
	WHITE/BF	OWN
NOTES:		
1. CONSTRUCTION: CONDUCTOR: 26 AWG STRANDED BARE COPPER	NOM. DIA	м.
INSULATION MATERIAL: FOAMED-PE PAIRS: COLOR CODED SINGLES TWISTED INTO PAIRS	.042" ±.002"[1.0	06±.05MM]
SHIELD(PAIR): AN ALUMINUM POLYESTER FOIL SHIELD, 25% OV OUTER SHIELD: TINNED COPPER BRAID, 60% COVERAGE	ERLAPPING (ALUMINUM OUT)	
JACKET: PVC, COLOR SEE CHART	0.236" ± .008"[6.	0 ± 0.20mm]
2. PHYSICAL PROPERTIES: OPERATING TEMPERATURE RATING: -10 ° C TO +75 ° C		
STORAGE TEMPERATURE RATING: -20 ° C TO +75 ° C FLAME TEST:CMG		
3. ELECTRICAL CHARACTERISTICS: VOLTAGE RATING: 30V		
DIELECTRIC STRENGTH: 500VAC/MINUTE INSULATION RESISTANCE(FOAMED-PE):10MΩ-10m AT 20 ° C 50	00VDC	
CONDUCTOR RESISTANCE(26AWG): 150Ω/KM AT 20 ° C		
4. ENVIRONMENT PROTECT STANDARD: RoHS2.0 and REACH COMPLIANT		
L-COM, INC WWW.L-COM.COM VERIFIED TO TIA/EIA-568-B.2 6. PACKAGE:	2 CALO FAICH CURD 4FK ZOANNG S/FIF FVC KOHS	¥¥ ¥¥/ I I
MODEL NUMBER LENGTH COLOR	PACKAGING	
TSFC6-BLK-1000F 1000.0 FT BLACK (RAL9005)	SPOOL	
TSFC6-BLK-100F 100.0 FT BLACK (RAL9005)	POLYBAG	
TSFC6-BLK-500F 500.0 FT BLACK (RAL9005) TSFC6-GRY-1000F 1000.0FT GRAY (RAL7035)	SPOOL SPOOL	
TSFC6-GRY-100F 100.0 FT GRAY (RAL7035)	POLY BAG	
TSFC6-GRY-500F 500.0FT GRAY (RAL7035)	SPOOL	
UNLESS OTHERWISE SPECIFIED,	APPROVALS DATE RAWN BY ZHANG 12/11/2020	50 HIGH STREET NORTH ANDOVER, MA
	HECKED BY an INFINIT® brand	01845
	SUTTADAURO 12/11/2020 TELECOM	MODULAR
ALL OTHER DIMENSIONAL TO A TO A ALL OTHER DIMENSIONAL TO FANCES: X = .2 [5.08] .XX = .005 [.13]	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY CATG S/FTP 4PR/2	
	COLOR VARIATIONS SIZE FSCM NO. DWG. NO.	REV.
	A 43321 SCALE: NONE CAD FILE: TSFC6.SLDDRW	TSFC6 A