

7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable



EZ-600-716M-X



Times Microwave Systems Connector Specification

Configuration

- 7/16 DIN Male Connector
- 50 Ohms
- Straight Body Geometry
- LMR-600, LMR-600-DB, LMR-600-FR, 600-Series Interface Type
- Crimp/Non-Solder Contact Attachment
- 1 1/4 in Hex

Features

- Designed to industry standard interface dimensions
- Quality body materials and plating
- Crimp/Non-Solder Contact attachment
- Operates to 3 GHz

Applications

- RF Boxes and components
- RF Test systems
- General Purpose RF Interconnect
- Laboratory applications

Description

L-com's 7/16 DIN Male connector for LMR-600, LMR-600-DB, LMR-600-FR and 600-Series coax uses a Crimp/Non-Solder Contact attachment method. This 7/16 DIN connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our 7/16 DIN Male connector operates up to a maximum frequency of 3 GHz.

The specifications and a basic dimensional drawing for EZ-600-716M-X Male 7/16 DIN connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 3 | GHz |
| VSWR | | | 1.15:1 | |
| Return Loss | | | 0.05 | dB |
| Operating Voltage (AC) | | | 2,500 | Vrms |

Mechanical Specifications

| | | |
|---------------|-----------|-----------|
| Width/Dia. | 1.25in | [31.75mm] |
| Weight | 0.298lbs | [135.17g] |
| Mating Torque | 221in-lbs | [24.97Nm] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable EZ-600-716M-X](#)

7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable



EZ-600-716M-X



Material Specifications

| Description | Material | Plating |
|-----------------|----------|------------------------------|
| Contact | Copper | Silver 196µ in. minimum |
| Insulation | PTFE | |
| Outer Conductor | Brass | Tri-Metal 78µin. minimum |
| Body | Brass | Tri-Metal 78µ in. minimum |
| Coupling Nut | Brass | Nickel 196µ in. minimum |

Environmental Specifications

Temperature

Operating Range -55°C to +155°C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable EZ-600-716M-X

URL: <https://www.l-com.com/7-16-DIN-Male-Connector-Crimp-Non-Solder-Contact-Attachment-For-LMR-600-LMR-600-DB-LMR-600-FR-600-Series-Cable-EZ-600-716M-X.p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

7/16 DIN Male Connector Crimp/Non-Solder Contact Attachment For LMR-600, LMR-600-DB, LMR-600-FR, and 600-Series Cable

L-com CAD Drawing

