

1710-4200 MHz 20 dBi Gain Mesh Parabolic 2x2 MIMO Dish Antenna - 2 x Type N Male Connector

HG-1742DP-17EG-NM



Features

- · Low Windload Mesh Design
- +/-45 Slant Polarization
- 17 dBi Gain

Applications

- LTE,5G,CBRS
- Cellular networks

- 2x2 MIMO
- Type N Male Connector
- DAS (Distributed Antenna Systems)
- IEEE 802.11b/g/n WiFi applications

Description

The L-com HG-1742DP-20EG-NM is a high performance LTE / CBRS Mesh Parabolic Dish antenna specifically designed for cellular networks. L-com's HG-1742DP-20EG-NM has 20 to 22 dBi gain and can be used to broadcast Cellular LTE signals. The HG-1742DP-20EG-NM operates from 1710 to 4200 MHz which is ideal for 5G, LTE, PCS, UMTS, CBRS applications including LoRA, LTE-M, and NB-IOT. The Multi-Band design of the L-com HG-1742DP-20EG-NM antenna eliminates the need to purchase different antennas for each frequency. This simplifies installations since the same antenna can be used for a wide array of telecommunication applications where wide coverage is desired.

The HG-1742DP-20EG-NM from L-com has directional patterns with Dual Slant (±45°) polarization and features 2 x Type N Male connectors. The Type N connectorized HG-1742DP-20EG-NM antenna from L-com is designed specifically for outdoor operation and is ideal for point to point use in large open areas such as base station installations or cellular backhaul. The included mounting bracket and hardware makes this antenna very easy to install. This LTE / CBRS Mesh Parabolic Dish antenna just like our wide selection of superior quality RF parts, ship same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other L-com products."

Configuration

Design
Band Type
Radiation Pattern
Polarization
Connector Type
Lightning Protection

Grid Multi Directional ±45 Deg. Slant N Male DC Ground

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	1,700		4,200	MHz
Frequency Range Impedance		50		Ohms
Gain		17		dBi
Front to Back Ratio	28			dB
Input Power			50	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1710-4200 MHz 20 dBi Gain Mesh Parabolic 2x2 MIMO Dish Antenna - 2 x Type N Male Connector HG-1742DP-17EG-NM



1710-4200 MHz 20 dBi Gain Mesh Parabolic 2x2 MIMO Dish Antenna - 2 x Type N Male Connector

HG-1742DP-17EG-NM



Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	1.71 to 2.69	3.3 to 4.2				GHz
Gain	17	19				dBi
Horizontal HPBW	25	15				Degrees
Vertical HPBW	25	15				Degrees
VSWR Max	2.5:1	2.5:1				

Mechanical Specifications

Size

 Length
 16 in [406.4 mm]

 Width
 16 in [406.4 mm]

 Height
 8 in [203.2 mm]

Mounting Mast Diameter 1.18 to 2.75 in [29.97 to 69.85 mm]

Weight 2.2 lbs [997.9 g]

Environmental Specifications

Temperature

Operating Range -40 to +70 deg C
Mechanical Tilt 20 Degrees

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

1710-4200 MHz 20 dBi Gain Mesh Parabolic 2x2 MIMO Dish Antenna - 2 x Type N Male Connector from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

