

617 to 7125 MHz Wi-Fi 6E Omni Antenna, 3 dBi Gain, NMO Connector White



## LCANOM1055

### Features

- NMO Connector
- Vertical Polarization
- Outdoor Rated Omnidirectional Antenna
- 2.4 GHz, 5 GHz, 6 GHz Wi-Fi Bands
- 5 dBi gain
- 100 Watt Max Power

### Applications

- Infotainment systems, Routers, Wi-Fi hotspots, HD video transmission, Gateways, Dash cameras, Public transportation
- Connected cars or self-driving cars, Fleet management, Logistics
- Public Safety Networks
- IoT, Industrial IoT, Zigbee, Bluetooth, Wi-Fi

### Description

The LCANOM1055 Wi-Fi 6e Omni Antenna from L-com is a high performance omnidirectional antenna designed for the 617 MHz to 7125 MHz bands and is available to ship same day. It is a UV protected, outdoor rated antenna with omni-directional pattern. The LCANOM1055 is ideally suited for 802.11 protocols including 802.11ax as well as IoT, Zigbee and Bluetooth.

The L-com high performance omni LCANOM1055 is a rugged antenna providing broad coverage, low latency, increased network capacity and 3 dBi gain. This NMO omnidirectional antenna is suitable for commercial radios and access points in public and private networks that are equipped with NMO Type connectors.

This Wi-Fi 6e LCANOM1055 omni antenna with NMO connectors, as well as our wide selection of superior quality RF parts, ships same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other L-com products.

### Configuration

Design	Omni
Application Band	Wi-Fi 6E
Band Type	Dual
Radiation Pattern	Omnidirectional
Polarization	Vertical
Connector Type	NMO
Number of Ports	1

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	617		7,125	MHz
Input VSWR			2.5:1	
Impedance		50		Ohms
Gain Variation		±0.5		dBi
Input Power			100	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[617 to 7125 MHz Wi-Fi 6E Omni Antenna, 3 dBi Gain, NMO Connector White LCANOM1055](#)

617 to 7125 MHz Wi-Fi 6E Omni Antenna, 3 dBi Gain, NMO Connector White



**LCANOM1055**

**Specifications by Band**

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.617 to 0.96	1.71 to 7.125				GHz
Gain	2	5				dBi
Horizontal HPBW	360	360				Degrees
Vertical HPBW	60	45				Degrees

**Mechanical Specifications**

Radome Material	UV Resistant ABS
<b>Size</b>	
Length	3.75 in [95.25 mm]
Width	1.6 in [40.64 mm]
Height	1.6 in [40.64 mm]
Weight	0.45 lbs [204.12 g]

**Environmental Specifications**

<b>Temperature</b>	
Operating Range	-40 to +85 deg C
Humidity	5 to 95

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

617 to 7125 MHz Wi-Fi 6E Omni Antenna, 3 dBi Gain, NMO Connector White from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

