

SMB Plug to SMB Jack Bulkhead Mount using RG316 Coax Cable 48 Inches



LCCA9851-48

Configuration

· Connector 1: SMB Plug

· Connector 2: SMB Jack Bulkhead

• Cable Type: RG316

Features

VSWR of 1.4:1

Applications

- Military
- Aerospace

- · Wireless Communications
- · General Purpose Test

Description

L-com's LCCA9851-48 is a SMB plug to SMB jack bulkhead mount using RG316 coax cable 48 inches and ships same-day. Our L-com SMB to SMB cable assembly has a plug to jack gender configuration with RG316 series coax and operates to 3 GHz. L-com's RF cable assembly with SMB bulkhead interface enables system designers to have external connections on their product enclosures or to be used for other rack mount and panel mount applications.

Custom versions of this SMB plug to SMB jack cable, along with the rest of L-com's other RF assemblies, can also be built and shipped same day. Other available RF cable assembly value added services from L-com include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly. Contact a sales representative for testing or custom RF cable quotes. Part number LCCA9851-48 L-com SMB Plug to SMB Jack Bulkhead Mount using RG316 Coax Cable 48 Inches data sheet PDF includes details of the RF product specifications, CAD drawing(s) and dimensions below.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Velocity of Propagation		69		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.64	0.84	1.16	1.72	2.52	dB

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.2 dB per connector



SMB Plug to SMB Jack Bulkhead Mount using RG316 Coax Cable 48 Inches



LCCA9851-48

Mechanical Specifications

Cable Assembly

Length* 48 in [121.92 cm]
Weight 0.162 lbs [73.48 g]

Cable

Cable TypeRG316Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE

Connectors

Description	Connector 1	Connector 2	
Туре	SMB Plug	SMB Jack Bulkhead	
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Beryllium Copper, Gold over Copper	Bronze, Gold over Copper	
Body Material and Plating	Bronze, Copper-Tin-Zinc Alloy	Bronze, Copper-Tin-Zinc Alloy	

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

· Values at 25°C, sea level.




SMB Plug to SMB Jack Bulkhead Mount using RG316 Coax Cable 48 Inches



LCCA9851-48

How to Order



Example: LCCA9851-12 = 12 inches long cable

LCCA9851-100cm = 100 cm long cable

SMB Plug to SMB Jack Bulkhead Mount using RG316 Coax Cable 48 Inches from L-com has same day shipment for domestic and International orders. L-com is a leading manufacturer of wired and wireless connectivity products and committed to in-stock availability and same day shipping. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

