

4-Slot, TRB, Plug, 78 Ohm, Terminator, with 6" Chain



LCCN10-06403-036

Applications

TRB PLUG

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		500	MHz
Impedance		78		Ohms

Mechanical Specifications

Size

 Length
 1.76 in [44.7 mm]

 Width
 0.56 in [14.22 mm]

 Height
 0.56 in [14.22 mm]

 Weight
 0.0625 lbs [28.35 g]

Configuration

Connector TRB 4-Slot Plug
Connector Specification MIL-STD-1553

Material Specifications

Description	Material	Plating	
Connector 1 Contact	Bronze	Gold 30 micro inches ASTM-B-488	
Gasket	Rubber		
Body	Brass	Nickel ASTM-B-733	

Environmental Specifications

Temperature

Operating Range -55 to +200 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 4-Slot, TRB, Plug, 78 Ohm, Terminator, with 6" Chain LCCN10-06403-036



4-Slot, TRB, Plug, 78 Ohm, Terminator, with 6" Chain



LCCN10-06403-036

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

4-Slot, TRB, Plug, 78 Ohm, Terminator, with 6" Chain from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 4-Slot, TRB, Plug, 78 Ohm, Terminator, with 6" Chain LCCN10-06403-036

URL: https://www.l-com.com/4-slot-trb-plug-78-ohm-terminator-w-6"-chain-fmtr10-06403-036-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

