

SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178



LCCN3023

Configuration

- SMB Jack Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry
- RG178 Interface Type
- Crimp/Solder Attachment
- Bulkhead

Features

- Designed to industry standard interface dimensions
- Quality body materials and plating
- Crimp/solder attachment
- Operates to 2 Ghz

Applications

- RF Boxes and components
- RF Test Systems
- General Purpose RF Interconnect
- Laboratory applications

Description

L-com's SMB jack bulkhead connector for RG178 coax uses a crimp/solder attachment method. This SMB connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our SMB jack bulkhead connector operates up to a maximum frequency of 2 GHz. &&The specifications and a basic dimensional drawing for LCCN3023 jack bulkhead SMB connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable, L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2	GHz
VSWR			1.5:1	
Operating Voltage (AC)			250	Vrms

Mechanical Specifications

Size

- Length 0.845 in [21.46 mm]
- Width/Dia. 0.237 in [6.02 mm]
- Weight 0.009 lbs [4.08 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178 LCCN3023](#)

SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178



LCCN3023

Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum

Environmental Specifications

Temperature

Operating Range -40 to +60 °C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178 from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178 LCCN3023

URL: <https://www.l-com.com/smb-jack-standard-rg178-connector-lccn3023-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

SMB Jack Bulkhead Connector Crimp/Solder Attachment For RG178

L-com CAD Drawing



L-com™
an INFINITE brand

50 High Street, West Mill, 3rd Floor, Suite #30
North Andover, MA 01845 USA
Phone: 1.800.341.5266 | 1.978.682.6936
Fax: 1.978.689.9484
Website: www.L-com.com
E-mail: CustomerService@L-com.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGNATION ON THIS
DRAWING IS THE PROPERTY OF
L-COM GLOBAL CONNECTIVITY.
ALL RIGHTS RESERVED.

SHEET 1 OF 1
SCALE N/A

ITEM NO. LCCN3023
REV A

SIZE A CAGE CODE A 43321 DRAWN BY DFRISIELLO