

BNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG178, .480 inch D Hole



LCCN3030

Configuration

- · BNC Female Connector
- 50 Ohms
- Straight Body Geometry

Features

- · Designed to industry standard interface dimensions
- · Quality body materials and plating

Applications

- · RF Boxes and components
- RF Test Systems

- RG178 Interface Type
- Crimp/Solder Attachment
- Bulkhead
- Crimp/solder attachment
- · Operates to 4 Ghz
- General Purpose RF Interconnect
- · Laboratory applications

Description

L-com's BNC female bulkhead connector for RG178 coax uses a crimp/solder attachment method. This BNC connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our BNC female bulkhead connector operates up to a maximum frequency of 4 GHz. &&The specifications and a basic dimensional drawing for LCCN3030 female bulkhead BNC connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable, L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz

Mechanical Specifications

Size

 Length
 1.072 in [27.23 mm]

 Width/Dia.
 0.689 in [17.50 mm]

 Weight
 0.037 lbs [16.78 g]

Material Specifications

Description	Material	Plating	
Contact	Phosphor Bronze	Gold	
Insulation	PTFE		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG178, .480 inch D Hole LCCN3030



BNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG178, .480 inch D Hole



LCCN3030

Body	Brass	Nickel

Environmental Specifications
Temperature
Operating Range

-40 to +85 °C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

BNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG178, .480 inch D Hole from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG178, .480 inch D Hole LCCN3030

URL: https://www.l-com.com/bnc-female-standard-rg178-connector-lccn3030-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

