

18 GHz SMA Female Field Replaceable Connector With  
EMI Gasket 2 Hole Flange Mount .012 inch Pin



**LCCN3200**

**Configuration**

- SMA Female Connector
- MIL-STD-348
- 50 Ohms
- Straight Body Geometry
- .012 inch Pin Interface Type
- Field Replaceable Attachment
- 2 Hole Flange

**Description**

The L-com LCCN3200 SMA female connector has a passivated stainless steel body for telecommunications, data communication, general-purpose test, industrial fields, and rack and panel mount applications. This RF connector has a straight body style and beryllium copper contact with gold plating. This threaded standard coaxial connector works on a maximum frequency of 18 GHz and provides an excellent maximum VSWR of 1.25.

The 18 GHz SMA connector is available in a 0.375-inch length, 0.223-inch width, and 0.625-inch height. This straight coaxial connector has 2 hole flange mount. The 0.012 inch pin field replaceable contact connector allows developers to configure and customize their signal connections however they desire. This SMA connector with field replaceable attachment has a high-quality construction and an impedance of 50 ohms.

The LCCN3200 0.012 inch pin field replaceable contact RF connector with 2 hole flange mount facilitates RF connectivity between boards and several microwave components including filters, attenuators, mixers, and oscillators. This 18 GHz passivated stainless steel coaxial connector comes with PTFE insulation. The SMA female connector weighs 0.013 pounds and is most used in USB software-defined radio dongles, handheld radios, mobile phone antennas, Wi-Fi antenna systems, and microwave systems.

L-com has the largest in-stock selection of RF and coaxial connectors with same-day shipping for domestic and international orders. We currently have a variety of antenna, audio/video, Ethernet, fiber optic, and USB connectors in our portfolio that are ready to ship today. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the high-quality RF connector that meets your requirements.

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.25:1	
Operating Voltage (AC)			335	Vrms

**Mechanical Specifications**

**Size**

Length	0.375in	[9.53mm]
Width/Dia.	0.223in	[5.66mm]
Height	0.625in	[15.88mm]
Weight	0.013lbs	[5.9g]
Mating Cycles	500Cycles	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[18 GHz SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .012 inch Pin LCCN3200](#)

18 GHz SMA Female Field Replaceable Connector With  
EMI Gasket 2 Hole Flange Mount .012 inch Pin



**LCCN3200**

**Material Specifications**

Description	Material	Plating
Contact	Beryllium Copper	Gold 50µ in. minimum
Insulation	PTFE	
Outer Conductor	Passivated Stainless Steel	
Body	Passivated Stainless Steel	

**Environmental Specifications**

**Temperature**

Operating Range -65deg C to +165deg C

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

18 GHz SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .012 inch Pin from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 18 GHz SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .012 inch Pin LCCN3200

URL: <https://www.l-com.com/18-ghz-sma-female-field-replaceable-connector-emi-gasket-2-hole-flange-mount-.012-inch-pin-lccn3200-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document. The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

# 18 GHz SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .012 inch Pin

## L-com CAD Drawing

