

TNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG174, RG316, RG188, LMR-100, 0.100 inch, .480 inch D Hole



## LCCN45909

# Configuration

- · TNC Female Connector
- MIL-STD-348A
- 50 Ohms
- · Straight Body Geometry

#### **Features**

- · Max. Operating Frequency 1 GHz
- · Good VSWR of 1.5:1

## **Applications**

- · General Purpose Test
- · Rack and Panel Mount Applications

- RG174, RG316, RG188, LMR-100, .100 inch Interface Type
- Crimp/Solder Attachment
- Bulkhead
- · Gold Plated Brass Contact
- · 30 µin minimum contact plating
- · Custom Cable Assemblies

## **Description**

L-com's LCCN45909, TNC, Standard, Connector is part of our full line of RF components available for same-day shipping. Our TNC female connector operates up to a maximum frequency of 1 GHz and offers good VSWR of 1.5:1. This TNC bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. Our TNC female bulkhead connector LCCN45909 datasheet specifications and drawing with dimensions are shown below in this PDF. L-com's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, L-com has the right connector for the job. L-com can also expertly build your custom cable assemblies for you and ship same-day.

# **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
VSWR			1.5:1	
Operating Voltage (AC)			500	Vrms

# **Mechanical Specifications**

Size

 Length
 1.43 in [36.20 mm]

 Width
 0.69 in [17.50 mm]

 Weight
 0.05 lbs [20.41 g]

## **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold
		30 μin minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG174, RG316, RG188, LMR-100, 0.100 inch, .480 inch D Hole LCCN45909



TNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG174, RG316, RG188, LMR-100, 0.100 inch, .480 inch D Hole



## LCCN45909

Insulation	PTFE	
Body	Brass	Nickel
		100 μin minimum
		100 μπ ππιπαπ

# **Environmental Specifications**

**Temperature**Operating Range

-65deg C to +165deg C

**Compliance Certifications** (see product page for current document)

## **Plotted and Other Data**

TNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG174, RG316, RG188, LMR-100, 0.100 inch, .480 inch D Hole from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Female Bulkhead Mount Connector Crimp/Solder Attachment for RG174, RG316, RG188, LMR-100, 0.100 inch, .480 inch D Hole LCCN45909

URL: https://www.l-com.com/tnc-female-bulkhead-mount-connector-crimp-solder-attachment-rg174-rg316-rg188-lmr-100-0.100-inch-.480-inch-d-hole-lccn45909-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

# **L-com CAD Drawing**

