

Photoelectric Sensor, M12 x 60mm, PNP NO+NC, Diffuse Reflection 0.3 meter Range, 2 meter 4-wire Cable, IP67, Brass

PXPEM12-PKHX3

Features

- · Specialized IC
- IP67 Protection
- · Easy Installation

Applications

- · Industrial Automation
- Automotive
- Manufacturing

- · Wide Selection of Output Options
- Steady Performance
- · Broad Dection Range
- · Food and Beverage
- · Warehouse Automation
- Robotics

Description

The L-com PXPEM12-PKHX3 is a photoelectric proximity sensor designed to determine the proximity, absence, or presence of an item using a light transmitter. This photoelectric sensor offers a quick response PNP NO+NC output via a 2 meter 4-wire cable for connection. Our IoT sensor has stable performance due to a specialized integrated circuit. Make your online purchase right now to take advantage of our same-day shipping.

The PXPEM12-PKHX3 IoT sensor is IP67 protected and has a 2 meter 4-wire connecting cable. This M12 x 60mm threaded photoelectric proximity sensor requires a power supply voltage of 10 to 36 VDC. The photoelectric sensor has reliable performance making it suitable for warehouse and industrial automation, manufacturing, and food and beverage industries. This PNP NO+NC IoT sensor with a 2 meter 4-wire connecting cable has a fast response time, which allows it to detect small objects.

Our IoT sensor is constructed of M12 nickel-plated brass housing. The M12 x 60mm threaded diffuse photoelectric proximity sensor has a PNP NO+NC electrical connection and is used for the direct detection of objects. This photoelectric proximity sensor has a 0.3 meter sensing distance. Our photoelectric sensor is 12 mm in diameter and has a threaded barrel for easy installation and adjustment.

L-com has the largest in-stock selection of IP67-rated photoelectric proximity sensors with same-day shipping for domestic and international orders. We currently have a variety of IoT products in our portfolio that are ready to ship today. For further information on similar products, our expert technical support and knowledgeable sales team can help you get a high-quality photoelectric sensor with PNP NO+NC output as per your requirements.

General Specifications

Sensing Type
Design Type
Output Type
Sensing Distance
Supply Voltage
Hysteresis
IP Rating

Housing Material Connection Method Diffuse Reflection

M12 PNP 10 to 300 mm

10-36 VDC 15 %

IP67

Brass Nickel Plated 2M 4-wire cable

Environmental Specifications

Temperature

Operating Range

0 to +55 deg C



Photoelectric Sensor, M12 x 60mm, PNP NO+NC, Diffuse Reflection 0.3 meter Range, 2 meter 4-wire Cable, IP67, Brass

PXPEM12-PKHX3

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Photoelectric Sensor, M12 x 60mm, PNP NO+NC, Diffuse Reflection 0.3 meter Range, 2 meter 4-wire Cable, IP67, Brass from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: https://www.l-com.com/photoelectric-sensor-m12-x-60mm-pnp-no-plus-nc-diffuse-reflection-0.3-meter-range-2-meter-4-wire-cable-ip67-brass-pxpem12-pkhx3-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

PXPEM12-PKHX3 CAD Drawing

Photoelectric Sensor, M12 x 60mm, PNP NO+NC, Diffuse Reflection 0.3 meter Range, 2 meter 4-wire Cable, IP67, Brass

