

SMA Male Connector Crimp/Solder Attachment for LMR-200, LMR-200-DB, LMR-200-FR, and 200-Series Cable



TC-200-SM-SS-X

Times Microwave Systems Connector Specification

Configuration

- · SMA Male Connector
- MIL-STD-348
- 50 Ohms
- · Straight Body Geometry

- LMR-200, LMR-200-DB, LMR-200-FR, 200-Series Interface Type
- Crimp/Solder Attachment
- 5/16 Inch Hex

Features

- · Designed to industry standard interface dimensions
- · Quality body materials and plating

· Crimp/Solder attachment

Applications

- · RF Boxes and components
- · RF Test systems

- · General Purpose RF Interconnect
- · Laboratory applications

Description

L-com's SMA Male connector for LMR-200, LMR-200-DB, LMR-200-FR and 200-Series coax uses a Crimp/Solder attachment method. This SMA connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our SMA Male connector operates in the frequency range supported by LMR-200 coax.

The specifications and a basic dimensional drawing for TC-200-SM-SS-X Male SMA connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

Mechanical Specifications

Size

 Length
 1.00 in [25.40 mm]

 Width
 0.31 in [7.92 mm]

 Weight
 0.04 lbs [16.78 g]

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
		ASTM B488
Insulation	Teflon	
Body	Passivated Stainless Steel	
		SAE-AMS-2700
Coupling Nut	Passivated Stainless Steel	
		SAE-AMS-2700

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for LMR-200, LMR-200-DB, LMR-200-FR, and 200-Series Cable TC-200-SM-SS-X



SMA Male Connector Crimp/Solder Attachment for LMR-200, LMR-200-DB, LMR-200-FR, and 200-Series Cable



TC-200-SM-SS-X

Environmental Specifications

Compliance Certifications (see product page for current document)

Plotted and Other Data

SMA Male Connector Crimp/Solder Attachment for LMR-200, LMR-200-DB, LMR-200-FR, and 200-Series Cable from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for LMR-200, LMR-200-DB, LMR-200-FR, and 200-Series Cable TC-200-SM-SS-X

URL: https://www.l-com.com/SMA-Male-Connector-Crimp-Solder-Attachment-for-LMR-200-LMR-200-DB-LMR-200-FR-200-Series-Cable-TC-200-SM-SS-X-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

